KENYON KENYON

14089757501

P.07

Applicatio No.: 09/708,722

Response to Final dated October 16, 2006

Office Action dated June 16, 2006

OCT 1 6 2006 ney Docket No. 2207/9800

## LISTING OF THE CLAIMS

The listing of the claims will replace all prior versions and listing of claims in the application.

- 1. (Previously Presented) A cache comprising:
- a cache line to store an instruction segment further comprising a plurality of instructions stored in sequential positions of cache line in reverse program order.
- 2. (Previously Presented) The cache of claim 1, wherein the instruction segment is an extended block.
- 3. (Previously Presented) The cache of claim 1, wherein the instruction segment is a trace.
- 4. (Previously Presented) The cache of claim 1, wherein the instruction segment is a basic block.
- 5. (Previously presented) A segment cache for a front-end system in a processor, comprising a plurality of cache entries to store instructions of instruction segments in reverse program order.
- 6. (Previously presented) Apparatus comprising:
  - an instruction cache system,
  - an instruction segment system, comprising:
  - a fill unit provided in communication with the instruction cache system.
  - the segment cache of claim 5 included therein, and

Applicatio No.: 09/708,722

Response to Final dated October 16, 2006

Office Action dated June 16, 2006

Attorney Docket No. 2207/9800

a selector coupled to an output of the instruction cache system and to an output of the segment cache.

- 7. (Previously presented) Apparatus of claim 6, wherein the instruction segment system further comprises a segment predictor provided in communication with the segment cache.
- 8. (Previously Presented) A method comprising:
  building an instruction segment based on program flow, and
  storing instructions of the instruction segment in a cache entry in reverse program order.
- 9. (Original) The method of claim 8, further comprising: building a second instruction segment based on program flow, and if the first and second instruction segments overlap, extending the first instruction segment to include non-overlapping instructions from the second instruction segment.
- 10. (Original) The method of claim 9, wherein the extending comprises storing the nonoverlapping instructions in the cache in reverse program order in successive cache positions adjacent to the instructions from the first instruction segment.
- 11. (Original) The method of claim 8, wherein the instruction segment is an extended block.
- 12. (Original) The method of claim 8, wherein the instruction segment is a trace.
- 13. (Original) The method of claim 8, wherein the instruction segment is a basic block.

Attorney Docket No. 2207/9800

Applicatio No.: 09/708,722

Response to Final dated October 16, 2006

Office Action dated June 16, 2006

14. (Previously presented) A processing engine, comprising:

a front end stage to build and store instruction segments, instructions provided therein in reverse program order, and

an execution unit in communication with the front end stage.

15. (Previously presented) The processing engine of claim 14, wherein the front-end stage comprises:

an instruction cache system,

an instruction segment system, comprising:

- a fill unit provided in communication with the instruction cache system,
- a segment cache, and

a selector coupled to an output of the instruction cache system and to an output of the segment cache.

- 16. (Previously presented) The processing engine of claim 15, wherein the instruction segments are extended blocks.
- 17. (Previously presented) The processing engine of claim 15, wherein the instruction segments are traces.
- 18. (Previously presented) The processing engine of claim 15, wherein the instruction segments are basic blocks.

Attorney Docket No. 2207/9800

Applicatio No.: 09/708,722

Response to Final dated October 16, 2006

Office Action dated June 16, 2006

19. (Previously presented) The processing engine of claim 15, wherein the instruction segment cache system further comprises a segment predictor provided in communication with the segment cache.